

Product data sheet "motion sprint 900 SL med"

motion sprint 900 SL med Device name:

Product type: Medical treadmill with lamella system

Manufacturer: Reha-Stim Medtec GmbH & Co. KG

F-MED-ML-900 Article number:

Monitor: 7" TFT – capacitive touch display, high-resolution colour display, loudspeaker for acoustic

biofeedback, inductive Qi charging cradle for mobile devices

Load range: 0.1-17 km/h, adjustable in 0.1 km/h increments

Inclination 0-15%

Optional: speed 0.1–22 km/h; reverse running direction up to -5 km/h, inclination 0-20%

Drive: 1100-watt brushless DC motor, toothed belt-driven lamella system, power supply: 230V/50-

60Hz/EEC, separate fuse required

Applied standards

(excerpt)

DIN EN ISO 20957-1 S-A-I, DIN EN 60601-1-2, DIN 957-6 S-A-I, DIN EN 60601 1-2

Medical device class: Class IIa in accordance with EU Regulation 2027/745 (MDR), Annex VIII

Certification/approval: **CE0123**

Application class

according to DIN EN ISO

20957-1:

S, I

Accuracy class according

to DIN EN ISO 20957-1:

A (high accuracy)

Operating conditions: Humidity: RH < 65%

Temperature: 0°C < t < 45°C

Display: Programme name, time, pulse, watts (in 1-watt increments), km/h, incline, HRV, km (in metres from

1-999, then in 10 m increments 1.00-99.99); K-Cal, Level

Heart rate measurement

compatibility:

Polar® auto connection system (Bluetooth® Low Energy & 5kHz), interference-free, with automatic

(dis)connection, backward compatible

Optional: ANT+ standard for compatibility with Garmin sensors and Polar® Verity Sense forearm

sensor

Wireless interfaces: Optional: Bluetooth®, NFC, RFID

Standard: Quick, Time, Heart rate (incline or speed controlled) Software programmes:

Optional: Watt sensitive, Therapy, Interval, K-Cal, Hill, Distance

Low-maintenance, energy-saving running surface, sturdy handrails Features:

Optional: underarm supports for children and adults, bar railing, safety bar, and much more

Max. user weight: 160 kg (optional: 200 kg)

173 x 76 x 145 cm (LxWxH) **Dimensions:**

Running surface: 155 x 50 cm

Step height: 28 cm

Noise level: < 75 dB (A)

Product net weight: approx. 149 kg

Transport weight: Depends on the type of packaging (land, sea or air freight)

Weight and dimensions may vary depending on optional equipment.

Frame colours depend on individual specifications. Subject to technical changes without prior notice.

Warning: The device may only be opened by a specialist.

For further information, please refer to the operating instructions.

(Issued: September 2025)