

Product Data Sheet „motion cross 600 med“

name of machine:	motion cross 600 med
manufacturer:	emotion fitness GmbH & Co. KG
part number:	F-MED-CR-600
monitor:	E900- monitor with casing, display and overlay
power range:	100-500 watt rpm – independent, up to 1000 watt rpm –dependent, rpm range 20-120 rpm, rpm limit preset to 80 rpm
brake system:	HBS-brake system (hybrid-brake-system); generator eddy-current-system; inertia n.a.
applied standards:	DIN EN ISO 20957-1, DIN EN ISO 20957-9, DIN EN 60601-1, DIN EN 60601-1-2
classification:	93/42 EEC class IIa
usage class:	S, I following DIN EN ISO 20957-1
accuracy class:	A (high accuracy) following DIN EN ISO 20957-1
ambient conditions:	humidity <65%; ambient temperature 0-45°C
display (resolutions):	LCD and Dot Matrix Display with following parameters: program number (1-11); time (00:00); pulse (optional); watt (1-999 in 1 watt-steps); km/h (0,1-99,9); rpm (15-120); km (in meter 1-999), after that in 10m-steps 1,00-99,99) ; k-cal (0,0-999,9); level (1-21)
pulse measurement:	coded Polar® receiver, earpulse optional
interfaces:	standard: RS232-interface, chipcard system optional: galvanically isolated RS232-interface, RFID, NFC, wireless network. Please consult on individual settings/needs in time.
programs:	standard: Quick, Watt, Pulse optional: Watt sensitive, Isokinetic, Therapy, Interval, Calorie, Hill, Random, Distance
maximum user weight:	standard: 150 kg optional: 200 kg
measurements:	ca. 200 x 65 x 165 cm (l/w/h)
net-weight:	ca. 103 kg
gross-weight:	ca. 123-161 kg (depending packaging and mode of transport)



Weight and dimensions may differ depending on accessories.
 Frame colour depending on individual specifications.
 Technical changes reserved.
 Warning: Only authorized service staff is allowed to open the unit.
 If you need further information please refer to user manual.
 (Issued: May 2021)