

Product Data Sheet "motion cross 600"

name of machine: motion cross 600

manufacturer: emotion fitness GmbH & Co. KG

part number: F-EF-CR-650

monitor: E900- monitor with casing, display and overlay

power range: 100-500 watt rpm – independent, up to 1000 watt rpm –dependent, rpm range 20-120 rpm,

rpm limit preset to 80 rpm

brake system: HBS-brake system (hybrid-brake-system); generator eddy-current-system; inertia n.a.

applied standards: DIN EN ISO 20957-1, DIN EN ISO 20957-9, DIN EN 60601-1, DIN EN 60601-1-2

usage class: S, I following DIN EN ISO 20957-1

accuracy class: A (high accuracy) following DIN EN ISO 20957-1

ambient conditions: humidity <65%; ambient temperature 0-45°C

display (resolutions): LCD and Dot Matrix Display with following parameters: program number (1-9); time (00:00);

pulse (optional); watt (1-999 in 1 watt-steps); km/h (0,1-99,9); rpm (15-120); km (in meter 1-

999), after that in 10m-steps 1,00-99,99); k-cal (0,0-999,9); level (1-21)

pulse measurement: coded Polar® receiver, earpulse optional

interfaces: standard: RS232-interface, chipcard system

optional: galvanically isolated RS232-interface, RFID, NFC, wireless network. Please consult on

individual settings/needs in time.

programs: standard: Quick, Time, Pulse

optional: Calorie, Hill, Random, Interval, Distance, Power

maximum user weight: standard: 150 kg

optional: 200 kg

measurements: ca. $200 \times 65 \times 165 \text{ cm} (I/w/h)$

net-weight: ca. 103 kg

gross-weight: ca. 123-161 kg (depending packaging and mode of transport)

Weight and dimensions may differ depending on accessories.

Frame colour depending on individual specifications.

Technical changes reserved.

Warning: Only authorized service staff is allowed to open the unit.

If you need further information please refer to user manual.

(Issued: May 2021)