

Product Data Sheet „motion stair 600“



name of machine:	motion stair 600
manufacturer:	emotion fitness GmbH & Co. KG
part number:	F-EF-MS-600
monitor:	E900- monitor with casing, display and overlay
power range:	4-27 m/min descending speed
brake system:	HBS-brake system (hybrid-brake-system); generator eddy-current-system; inertia n.a.
applied standards:	DIN EN ISO 20957-1, DIN EN ISO 20957-8, DIN EN 60601-1, DIN EN 60601-1-2
usage class:	S, I following DIN EN ISO 20957-1
accuracy class:	A (high accuracy) following DIN EN ISO 20957-1
ambient conditions:	humidity <65%; ambient temperature 0-45°C
display (resolutions):	LCD and Dot Matrix Display with following parameters: program number (1-8); time (00:00); pulse (optional); watt (1-999 in 1 watt-steps); km/h (0,1-99,9); rpm (15-120); km (in meter 1-999), after that in 10m-steps 1,00-99,99) ; k-cal (0,0-999,9); level (1-21)
pulse measurement:	coded Polar® receiver, handpulse and earpulse optionally
interfaces:	standard: RS232-interface, chipcard system optional: galvanically isolated RS232-interface, RFID, NFC, wireless network. Please consult on individual settings/needs in time.
programmes:	standard: Quick, Time, Pulse optional: Calorie, Hill, Random, Interval, Distance
maximum user weight:	150 kg
measurements:	ca. 105 x 65 x 160 cm (l/w/h)
net weight:	ca. 65 kg
gross weight:	ca. 88-124 kg (depending on packaging and mode of transport)

Weight and dimensions may differ depending on accessories.

Frame colour depending on individual specifications.

Technical changes reserved.

Warning: Only authorized service staff is allowed to open the unit.

If you need further information, please refer to user manual.

(Issued: July 2023)